



Type IC, Air-Tight & Wet

DESCRIPTION

10" Round Recessed LED With Integral Driver In Connection Box Commercial Grade Quality Built to Last


FEATURES & BENEFITS

2 1/4" Deep - Install Where Ceiling Space Is Limited Type IC Rated - No Housing Required Fast & Easy To Install - Save On Labor Driver Inside Connection Box - No Junction Box Needed Wet Location IP65 Approved

MOUNTING

Cut Hole In Ceiling And Snap Fixture In Opening With Attached Spring Clips. Ceiling Clearance Required: 2 1/4"

DIMENSIONS: ID 10" OD 12" Cut Out 10" to 11"



120V - 277V Driver Included 0-10V Dimmable



ORDERING GUIDE Example: LL10R - 30K - WH

	CCT	Trim Finish	
LL10R	-	-	
3000K	30K	WH	White
4000K	40K	BK	Black

10" Round Commercial Recessed LED 50W

Project:

Location:

Cat #: Qty:

Notes:

SPECIFICATION				
Applications	High Ceilings Recessed Mount			
Energy Used	50 W			
Color Temperature K	3000	4000		
Light Output Im	6500	6700		
Equivalent	100 W MH HPS			
Beam Angle	60°			
CRI	80			
Default Driver Input	120V-277V AC	0-10V Dimmable		
Optional Driver Input	347V AC	0-10V Dimmable		
Power Factor	0.95			
Junction Box Wire Capacity	Max 5 No 12 AWG or 8 No 14 AWG			
Approved Location	Insulated Ceilings, Wet Locations			
IP Rating	IP 65			
Air Tight	Yes			
Ambient Temperature	-40°F (-40°C) to +104°F (+40°C)			
Projected Life	70% Light Output at 50,000 Hours			
Certification	cULus, Energy Star			
Warranty	5 Year			

AVAILABLE TRIMS





ACCESSORIES



Sold Separately

Low Voltage Extensions 6ft cat # **BXC6** FT4 / CMR rated. Max 40 ft Allowed



Pendant Mount Kit cat # **PMK810**Includes Aircraft Cable & 6ft Extension



347V Input Driver 0-10V Dimmable
Order Separately as cat # LLL-LD50WH



Goof Ring Round White ID 10½"

OD14" cat# **GR10-14**, OD16" cat# **GR10-16**

Goof Ring Square White ID 10½"
OD14" cat# **GS10-14**, OD16" cat# **GS10-16**

COMPLIANCE







Type IC Air-Tight