

Woodland
Rigid Core Flooring

Specification

| | |
|-----------------|--|
| Product name: | Woodland |
| Floor type: | rigid core (SPC) |
| Structure: | 4.3mm total thickness 3mm rigid core 0.3mm wear layer (12 mil) 1.0mm EVA attached pad |
| Surface finish: | Wood grain finish with ceramic bead and enhanced scratch resist UV coating |
| Joint profile: | Licensed Unilin angle on sides and New Drop and Tap on the end joints |
| Installation: | Float, glue down |
| Plank size: | 48" x 7" |
| Packaging: | 8 pieces / carton 18.90 sf / carton 85 cartons / pallet 20 pallets / container 40 lbs / carton |
| Warranty: | Lifetime Residential 5 year Commercial |

Performance Specification:

| | | | |
|--------------------------------|--------------------|--|------------------------|
| Dimensional Stability | ASTM F2199-09 | $\leq 0.166\%$ | Surpasses requirements |
| Static Load Limit | ASTM F970-17 | $\leq 0.005"$ | Surpasses requirements |
| Residual Indentation | ASTM F1914-07 | Average $\leq 8\%$ Maximum $\leq 8\%$ | Surpasses requirements |
| Static Coefficient of Friction | ASTM C1028-07 | N/A | >0.6 wet and dry |
| Resistance to Light | ASTM F1515-15 | Average $\Delta E \leq 8.0$ | Surpasses requirements |
| Resistance to Heat | ASTM F1514-03 | Average $\Delta E \leq 8.0$ | Surpasses requirements |
| Heavy Metals | EN 71-3 Part3:1994 | | None detected |
| Phthalate content | CPSC-CH-C1001-09.3 | | None detected |
| Critical Radiant Flux | ASTM E648-17a | Class 1: $\geq 0.45 \text{ W/cm}^2$ | Surpasses requirements |
| Smoke Density | ASTM E662-17a | <450 flaming and Non-flaming | Surpasses requirements |
| Impact Sound (IIC) | ASTM E492-09 | N/A | IIC = 59 |